

# Victory Series 4 Channel 720p Surveillance Kit

Model: CVR4PACK



## Product Overview

The Securview Victory Series range is the ideal HD video over coax choice for new surveillance installations and for upgrades to existing analogue systems. Victory Series products utilise the HDCVI video transmission standard, delivering video, audio and data across a single coaxial cable (RG59 / RG6 75-3). This also allows for up to 500m transmission distances for 720p HD video streams using standard coaxial cable.

The CVR4PACK is a compact 4 channel surveillance system capable of 720p HD recording over coax cable at 25fps. It features a preinstalled HDD with 1TB of storage and has HDMI and VGA video outputs. This DVR also has comprehensive remote view (iOS, Android & Windows Phone) and backup functionality (USB/network).

The CVR4PACK includes 4 weatherproof, 3.6mm fixed lens (70°), 20m infrared range, 1.3 megapixel cameras that are ideal for use in a multitude of applications. They record at 720p (1280 x 720), almost 3x greater resolution compared to traditional D1 analogue systems (704 x 576) and up to 12x greater versus CIF (352 x 288).

Compatible with Victory Series products only. It does not include coaxial cable, splitters or camera power supplies. For new installs, see the Victory Series accessory kit (CVR4ACCPACK).

## Package Contents



Your Securview Victory Series dealer:

Specifications - Digital Video Recorder		
System	Main Processor	Embedded processor
	Operating System	Embedded Linux OS
	Video Input	4 channel BNC
	Audio Input	1 channel RCA
	Audio Output	1 channel RCA
Display	Video Output	1 HDMI / 1 VGA
	Preview Resolution	1920x 1080, 1280x 1024, 1280x 720, 1024x 768, 800x 600
	Display Split	1 / 4
	OSD	Title, time, video loss, camera lock, motion detection, recording
Recording	Video/Audio Compression	H.264 / G.711
	Record Resolution	Main stream: 720p (1280 x 720) / Sub stream: CIF (352 x 288)
	Record Rate	720p/D1 (1~25fps)
	Record Modes	Manual / Schedule (Regular [Continuous], MD) / Stop
Backup & Network	Backup Modes	USB Device / Network
	Ethernet	RJ-45 port (10/100M)
	Max. User Access	128 users
	Remote View	iOS (iPhone, iPad); Android devices, Windows Phone
Storage	Internal HDD	1TB preinstalled hard drive
Auxiliary	USB Interface	2 ports (1 Rear), USB2.0
	RS232	N/A
	RS485	1 port, for PTZ Control
General	Power Supply	DC12V/2A
	Operating Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
	Dimensions	325mm x 245mm x 45mm (Mini 1U)
	Weight	1.5kg (without HDD)
Specifications - Cameras		
Camera	Cameras Included	4 x VSCV11MPFBIR: 1.3MP Bullet
	Image Sensor	1/3"1.3 Megapixel CMOS
	Lens	3.6mm Fixed Lens
	Angle of View	70°
	Minimum Illumination	0.05 Lux at F1.2 (Colour) / 0 Lux IR Active
	Day/Night	Auto (ICR) / Colour / B&W
	Transmission Distance	Over 500m via 75-3 coaxial cable
	Video	Video Compression
Resolution		720p (1280x720) / D1 (704x576)
Frame Rate		720p (25fps)
Video Output		BNC CVI HD output / CVBS SD output (switchable)
General	Ingress Protection	IP66
	Vandal Resistant	No
	Maximum Infrared Range	20m
	Power Input	DC12V±10%
	Operating Environment	-30° to 60°C / RH95% (max)