

# Victory Series 8 Channel 720p Surveillance Kit

Model: CVR8PACK



## Product Overview

The Securview Victory Series range is the ideal HD video over coax choice for new surveillance installations and for upgrades to existing analogue systems. Victory Series products utilise the HDCVI video transmission standard, delivering video, audio and data across a single coaxial cable (RG59 / RG6 75-3 preferred). This also allows for up to 500m transmission distances for 720p HD video streams using standard coaxial cable.

The CVR8PACK is a compact 8 channel surveillance system capable of 720p HD recording over coax cable at 25fps. It features a preinstalled HDD with 2TB of storage and has HDMI and VGA video outputs. This DVR also has comprehensive remote view (iOS, Android & Windows Phone) and backup functionality (USB/network).

The CVR8PACK includes 8 weatherproof, 3.6mm fixed lens (70°), 20m infrared range, 1.3 megapixel cameras that are ideal for use in a multitude of applications. They record at 720p (1280 x 720), almost 3x greater resolution compared to traditional D1 analogue systems (704 x 576) and up to 12x greater versus CIF (352 x 288).

Compatible with Victory Series products only. It does not include coaxial cable, splitters or camera power supplies. For new installs, see the Victory Series accessory kit (CVR4ACCPACK).

## Package Contents



Your Securview Victory Series dealer:

| Specifications - Digital Video Recorder |                         |   |
|---|-------------------------|---|
| System                                  | Main Processor          | Embedded processor  |
|   | Operating System        | Embedded Linux OS   |
|   | Video Input             | 8 channel BNC   |
|   | Audio Input             | 1 channel RCA   |
|   | Audio Output            | 1 channel RCA   |
| Display                                 | Video Output            | 1 HDMI / 1 VGA  |
|   | Preview Resolution      | 1920x 1080, 1280x 1024, 1280x 720, 1024x 768, 800x 600            |
|   | Display Split           | 1/ 4/ 8   |
|   | OSD                     | Title, time, video loss, camera lock, motion detection, recording |
| Recording                               | Video/Audio Compression | H.264 / G.711   |
|   | Record Resolution       | Main stream: 720p (1280 x 720) / Sub stream: CIF (352 x 288)      |
|   | Record Rate             | 720p/D1 (1~25fps)   |
|   | Record Modes            | Manual / Schedule (Regular [Continuous], MD) / Stop               |
| Backup & Network                        | Backup Modes            | USB Device / Network  |
|   | Ethernet                | RJ-45 port (10/100M)  |
|   | Max. User Access        | 128 users   |
|   | Remote View             | iOS (iPhone, iPad); Android devices, Windows Phone                |
| Storage                                 | Internal HDD            | 2TB preinstalled hard drive                                       |
| Auxiliary                               | USB Interface           | 2 ports (1 Rear), USB2.0  |
|   | RS232                   | N/A   |
|   | RS485                   | 1 port, for PTZ Control   |
| General                                 | Power Supply            | DC12V/2A  |
|   | Operating Environment   | -10 ~+55°C / 10~90%RH / 86~106kpa                                 |
|   | Dimensions              | 325mm x 245mm x 45mm (Mini 1U)                                    |
|   | Weight                  | 1.5kg (without HDD)   |
| Specifications - Cameras                |                         |   |
| Camera                                  | Cameras Included        | 4 x VSCV11MPFBIR: 1.3MP Bullet / 4 x VSCV11MPDIR: 1.3MP Dome      |
|   | Image Sensor            | 1/3"1.3 Megapixel CMOS  |
|   | Lens                    | 3.6mm Fixed Lens  |
|   | Angle of View           | 90°   |
|   | Minimum Illumination    | 0.05 Lux at F1.2 (Colour) / 0 Lux IR Active                       |
|   | Day/Night               | Auto (ICR) / Colour / B&W   |
|   | Transmission Distance   | Over 500m via 75-3 coaxial cable                                  |
|   | Video                   | Video Compression   |
| Resolution                              |                         | 720p (1280x720) / D1 (704x576)                                    |
| Frame Rate                              |                         | 720p (25fps)  |
| Video Output                            |                         | BNC CVI HD output / CVBS SD output (switchable)                   |
| General                                 | Ingress Protection      | IP66  |
|   | Vandal Resistant        | No  |
|   | Maximum Infrared Range  | 20m   |
|   | Power Input             | DC12V±10%   |
|   | Operating Environment   | -30° to 60°C / RH95% (max)  |