



Model: DVR4ENTPACK6M

4 Camera DVR Kit with 1TB Hard Drive and 19" LCD Monitor



The DVR4ENTPACK6M is a complete 4 channel surveillance package. It includes a 19" LCD wide screen monitor and 4x 520TVL weatherproof cameras, making them ideal for any indoor or outdoor environment. The cameras also have 15m infrared range - perfect for areas with low light or for night recording. The DVR can record each camera at D1 resolution (704 x 576) in real-time (25 fps) and can be customised to automatically record over old footage, viewed over a windows PC network or viewed remotely over the Internet. All cabling, remote control and power supplies are included in the kit.

The included 1TB hard disk drive can record for approximately 16 weeks with all cameras set at D1 resolution at a recording rate of 6 frames per second, per camera.

The DVR4ENTPACK6 now supports Push Video notifications, allowing you to receive alarm and motion alerts on your smartphone over the internet - stay in the loop no matter where you are!

Don't wait for Email or SMS Alerts - Get Instant Notifications with Push Video

1. CAUGHT ON CAMERA

2. PUSH VIDEO NOTIFICATION

3. PUSH VIDEO ALERT

EagleEyes
Intruder Detected in Bedroom 1

View Dismiss

Package Contents

The DVR4ENTPACK6 is a complete 4 channel surveillance package and comes in its own retail-ready box. The kit includes:



1 x 4 Channel H.264 Stand Alone Digital Video Recorder With Push Video, Network Functionality, Remote Access & 1TB Hard Drive

- Advanced H.264 video compression technology
- Multiplex operation
- Long recording duration
- Intelligent video motion detection recording
- Remote network surveillance & backup functions
- Easy to operate like a VCR with buttons for play, record, FF, RW, pause, search, etc
- System auto recovery after power loss (blackout)
- Supports manual / timer / motion / alarm / remote recording functions
- Watermark function ensures authentication of the recorded images * Supports TCP/IP, PPPoE, DHCP and DDNS network connection
- The DVR4ENTPACK6 DVR is compatible with the Eagle Eyes iPhone Application, which allows you to connect to your DVR via your smartphone for real-time footage viewing.



4 x Weatherproof Infrared Bullet Cameras

- High Quality CCD image sensor for superior picture quality
- 520 TVL Resolution
- 15m infrared range for viewing in complete darkness
- Compact and weatherproof design (IP66) for use indoors and outdoors



1 x 19" LCD Monitor with LED backlight

- 16:9 Aspect Ratio
- 30,000:1 Contrast Ratio
- 1366x768 Resolution
- 5ms Response Time



1 x Monitor Connection Cable

- Allows you to connect the BNC monitor output from the DVR to the RCA video input on your TV / VCR

1 x Network Cable (Optional Use)

- Allows you to connect the LAN port on the DVR to your PC or network to facilitate remote viewing or backup functions



1 x Power Split Cable

- Allows you to connect 4 Cameras to 1 power supply

4 x Camera Connection Cables

- Combined DC power and video leads pre-terminated
- Allowing simple plug-in connection (no tools required)
- 2 x 10m, 1x 20m, 1 x 30m leads supplied



2 x Switch Mode Low Voltage Power Supplies

- 1 x 3Amp 12VDC supply for use with the power split cable to power all cameras
- 1 x 2Amp 19VDC power supply for use with the DVR Advanced Switch Mode Technology

4 x High-Vis UV Resistant Window Warning Stickers



Specifications: DVR4ENT6

| | |
|--------------------------------|---|
| Video Compression Format | H.264 |
| Video Input | 4 Channels |
| Audio Input / Output | 4 audio inputs, 1 audio output (mono) |
| Recording Resolutions | 704x576 (D1) / 704x288 / 352x288 |
| Recording Framerate | 100 fps |
| Maximum Resolution Recording | Real Time (25 fps) Recording at D1 (704 x 576) on All Four Channels |
| Hard Disk Storage | Accommodates 1 SATA HDD (capacity up to 2TB) / Built-in SATA Interface |
| Quick Search | Time/Motion/Alarm search mode |
| Recording Mode | Manual/Timer/Motion/Alarm/Remote |
| Multiplex Operation | Live display/Record/Playback/Backup/Network operations |
| USB Mouse Control | YES |
| Motion Detection Area | 16 x 12 grids per channel |
| Motion Detection Sensitivity | 3 adjustable parameters for accurate detection |
| Pre-alarm Recording | YES |
| Backup Device | USB 2.0 flash drive / Network |
| Ethernet | 10/100 Base-T. Supports remote control and live view via Ethernet |
| Web Interface | Licensed software "Video Viewer" / Internet Explorer, Mozilla Firefox, Safari, Opera or Google Chrome web browser / QuickTime player Web Interface (5 users access simultaneously) *Operating System: Windows 7 / Vista / XP / 2000 |
| Network Protocol | TCP/IP, PPPOE, DHCP and DDNS |
| Event Notification | Push Video, FTP & E-Mail |
| Push Video Enabled Devices | iPhone, iPad and Android |
| Mobile Surveillance | Yes: iPad, iPhone, Blackberry, Windows Mobile & Java |
| Picture Zoom | 2X digital zoom |
| PTZ Control | YES |
| Alarm I/O | 4 inputs (1 input for Push Video), 1 output |
| Key Lock (Password Protection) | YES |
| Video Loss Detection | YES |
| Video Adjustable | Hue / Saturation / Contrast / Brightness |
| Power | DC 19V |
| Operating Temperature | 10°C ~ 40°C |
| Dimensions (mm) | 343(W) x 59(H) x 223(D) |
| System Recovery | System auto recovery after power failure |



Specification: VSWFF15MIR520B

| | | | |
|-----------------------|---------------------------|-------------------------|-------------------------|
| Image Sensor | 1/3" CMOS + IR Cut filter | Video Output | 1 Vp-p / 75 Ohms |
| Horizontal Resolution | Colour: 520TVL | Lens | 3.6 mm Board Lens |
| Signal System | PAL | IR LEDs | 24 pieces 5 mm IR-LED |
| IR Distance | 15M | Waterproofing Criterion | IP66 |
| Minimum Illumination | 0.2 Lux /F2.0 | Power | DC12V±10% |
| Sync System | Internal | Working Temperature | -10°C ~ +50°C RH95% Max |
| S/N Ratio | More than 48dB | Dimensions | L170 x H69 x W65 mmmm |
| Electronic Shutter | 1/50~1/110,000 | Weight | 600g |



Specification: 19" Wide Screen Monitor

| | |
|-------------------|---------------------|
| Aspect Ratio | 16:9 |
| Brightness | 300 cd/m2 (Typical) |
| Contrast Ratio | 30,000:1 |
| Resolution | 1366x768 |
| Response Time | 5ms (Typical) |
| Size | 19" Wide |
| Supported Colours | 16.7M Colors |
| Viewing Angle | H:170°, V:160° |

Call: 02 9671 6711 • Email: sales@rhino.com.au • www.rhino.com.au



Head Office
 Mon - Fri: 8:30am - 5pm
 9 Hannabus Place, McGraths Hill,
 NSW 2756 Australia
 Fax: (02) 4577 4885

Haberfield Branch
 Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
 223 Ramsay Street, Haberfield,
 NSW 2045, Australia
 Fax: (02) 9799 2024

Villawood Branch
 Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
 71 Middleton Road, Villawood,
 NSW 2163, Australia
 Fax: (02) 9743 8590