

MONITOR, OBSERVE, RECORD YOUR COMPLETE CCTV SOLUTION IN ONE KIT



Stay in touch everywhere! Live video via your smartphone!

Watchguard DVR

-

Mobile Mobile iPhone symbian BlackBerry

Digital Video Recorder with 4 Surveillance Cameras

DVR4EONPACK

-- Watchguard ----

The Watchguard DVR4EONPACK provides effortless CCTV installation and operation without compromising on functionality or cost. Delivered in one easy kit, it takes only a few steps to be up and running. Connect to a monitor or TV and the Internet to view on your PC or smartphone.



Your Complete DVR Kit Includes:

- 4 Channel H.264 Digital Video Recorder
- Installed 1TB Hard Disk Drive
- 4x Day / Night Weatherproof Colour Cameras
- Power Supplies & 18m Camera Connection Cables
- USB Mouse and Remote Control



*Apple iPhone 4 is not included in DVR4EONPACK. Monitor is optional and not included in this offer. All products, logos, trademarks and names are property of their respective owners.

DVR4EONPACK Specifications

SPECIFICATION	DVR4EONPACK
Operating System	Embedded Linux OS
Video Compression Format	Main Profile H.264 Compression
Video Input	4 Channels via BNC Connection
Video Output	1 Channel via BNC Connection / 1 Channel VGA Connection (1280x1024)
Display Picture	1/4
Multiplex Operation	Live\display\Playback\Recording\Backup\Mobile Phone Surveillance\Network Simultaneously
Display Resolution	PAL: D1 (704x576) NTSC: D1 (704x480)
Recording Mode	Manual\Timer\Motion Detection\Alarm
Recording Frame Rate	D1 at 50fps / HD1 at 100fps / CIF at 100fps Adjustable
Recording Resolution	PAL: D1 (704x576) / HD1 (704x288) / CIF (352x288) NTSC: D1 (704x480) / HD1 (704x240) / CIF (352x240)
Recording Playback	1/4 Channel Playback Simultaneously (Optional Playback Channel)
Recording Backup	USB / External Hard Disk / USB Writer / Network
Network Transmission	4 Channels Real-Time Network Transmission with CIF Resolution
Recording Play	Special Player, Support AVI File Format Conversion
JPEG Capture Function	Support / 3M Pixels at 10fps
Email Alarm	Send Pieces to a Designated Email
PTZ Functionality	Supports (PELCO-D, PELCO-P)
Hard Disk Drive	Supports 1 SATA HDD - Capacity up to 2TB
Network and Protocol	1 RJ-45 10/100M via Ehternet Supports TCP/IP, PPPOE, DHCP, DNS, DDNS, NTP, UPNP
Dual Stream	Support (Main and Secondary Interchange)
Group Play	Max Online Access - 5 Users
Watermarking Functionality	Support
Multi-Language Support	Support
Mobile Phone Surveillance	Supports Windows Mobile, Symbian, iPhone, Blackberry, Android
DST	Support
Power Supply	DC12V/3A
Working Temperature	0°C - 50°C
Working Humidity	10% - 90%
Dimensions	354mm (Width) x 230mm (Depth) x 45mm (Height)
SPECIFICATION	CAMERA Vauri and Dadar
Image Sensor	1/4'' CMOS
Horizontal Resolution	420 TVL
Total Pixel Array	648(H) x 488(∨)
Minimum Illumination	0.5 Lux / F2.0
TV System	PAL/NTSC
Lens Furnished	3.6mm Board Lens
Infrared Luminary	26 Pieces 5mm IR-LED, IR Range 20M
Wavelength	850nm
Waterproofing Criterion	1P66
S/N Ratio	More than 46dB
Electronic Shutter	NTSC: 1/60 ~ 1/100,000 PAL: 1/50 ~ 1/110,000
Gamma	0.45
White Balance	Auto
Gain Control	For more information, visit us at:
	Auto
Sync. System	
Video Output	1 Vp-p / 75 Ohms
Power Supply	
Operation Temperature	
Dimensions	
Weight	^{650g} Alarms & Surveillance