



Model: DVR8ENTPACK3

8 Camera DVR Kit with 1TB Hard Drive and Push Video Technology



* Monitor (LCD19LED) not included; available option.

The DVR can record at each camera at D1 resolution (704 x 576) in real-time (12 fps). You can adjust the recorder settings for both image quality and frame rate, and when the HDD is full, you can set the DVR to automatically record over the oldest footage. If connected to a windows PC network, footage can be viewed over the network using the included software. If the network has a high-speed Internet connection, footage can also be viewed remotely over the Internet. The software also enables footage to be backed up / archived from the DVR to a PC allowing storage on another HDD or burning to a DVD or CD.

The DVR8ENTPACK3 now supports Push Video notifications, allowing you to receive alarm and motion alerts on your smartphone over the internet, stay in the loop no matter where you are!

Don't wait for Email or SMS Alerts - Get Instant Notifications with Push Video



Package Contents

The DVR8ENTPACK3 is a complete 8 channel surveillance package. The kit includes:



1 x 8 Channel H.264 Stand Alone Digital Video Recorder With Push Video, Network Functionality, Remote Access & 1TB Hard Drive

- Advanced H.264 video compression technology
- Multiplex operation
- Long recording duration
- Intelligent video motion detection recording
- Remote network surveillance & backup functions
- Easy to operate like a VCR with buttons for play, record, FF, RW, pause, search, etc
- System auto recovery after power loss (blackout)
- Watermark function ensures authentication of the recorded images * Supports TCP/IP, PPPoE, DHCP and DDNS network connection



4 x Weatherproof Infrared Bullet Cameras

- High Quality CCD image sensor for superior picture quality
- 650 TVL Resolution
- 15m infrared range for viewing in complete darkness
- Compact and weatherproof design (IP66) for use indoors and outdoors



4 x Weatherproof Infrared Dome Cameras

- High Quality CCD image sensor for superior picture quality
- 650 TVL Resolution
- 15m infrared range for viewing in complete darkness
- Compact and weatherproof design (IP66) for use indoors and outdoors



1 x Monitor Connection Cable

- Allows you to connect the BNC monitor output from the DVR to the RCA video input on your TV / VCR

1 x Network Cable (Optional Use)

- Allows you to connect the LAN port on the DVR to your PC or network to facilitate remote viewing or backup functions

2 x Power Split Cable

- Allows you to connect 8 Cameras to 1 power supply



8 x Camera Connection Cables

- Combined DC power and video leads pre-terminated
- Allowing simple plug-in connection (no tools required)
- 2 x 10m, 2x 20m, 4 x 30m Leads Supplied



2 x Switch Mode Low Voltage Power Supplies

- 1 x 3Amp 12VDC supply for use with the power split cable to power all cameras
- 1 x 2Amp 19VDC power supply for use with the DVR Advanced Switch Mode Technology

4 x High-Vis UV Resistant Window Warning Stickers



Specifications: DVR8ENT3

Video Compression Format	H.264
Video Input	8 Channels
Video Output	Composite / VGA / HDMI
Audio Input / Output	4 audio inputs, 1 audio output (mono)
Recording Resolutions	704×576 (D1) / 704×288 / 352×288
Recording Framerate	100 fps at D1
Maximum Resolution Recording	12fps D1 (704 x 576) / Real Time Recording (25fps) at CIF (352 x 288)
Hard Disk Storage	Accommodates 1 SATA HDD (capacity up to 2TB) / Built-in SATA Interface
Quick Search	Time/Motion/Alarm search mode
Recording Mode	Manual/Timer/Motion/Alarm/Remote
Multiplex Operation	Live display/Record/Playback/Backup/Network operations
USB Mouse Control	YES
Motion Detection Area	16 × 12 grids per channel
Motion Detection Sensitivity	3 adjustable parameters for accurate detection
Pre-alarm Recording	YES
Backup Device	USB 2.0 flash drive / Network
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Web Interface	Licensed software "Video Viewer" / Internet Explorer, Mozilla Firefox, Safari, Opera or Google Chrome web browser / QuickTime player Web Interface (5 users access simultaneously) *Operating System: Windows 7 / Vista / XP / 2000
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS
Event Notification	Push Video, FTP & E-Mail
Push Video Enabled Devices	iPhone, iPad and Android
Mobile Surveillance	Yes: iPad, iPhone, Blackberry, Windows Mobile & Java
Picture Zoom	2X digital zoom
PTZ Control	YES
Alarm I/O	1 Input with Push Video, 1 output
Key Lock (Password Protection)	YES
Video Loss Detection	YES
Video Adjustable	Hue / Saturation / Contrast / Brightness
Power	DC 19V
Operating Temperature	10°C ~ 40°C
Dimensions (mm)	343(W) x 59(H) x 223(D)
System Recovery	System auto recovery after power failure



Specification: VSWFF15MIR650B

Image Sensor	1/3" CMOS + IR Cut filter
Horizontal Resolution	Colour: 650TVL
IR LEDs / Distance	24pcs / 15m
Lens	Fixed 3.6mm
Minimum Illumination	0.2 Lux /F2.0
Ingress Protection	IP66
Power	DC12V±10%
Dimensions	L170 x H69 x W65 mm



Specification: VSDF15MIR650VP

Image Sensor	1/3" CMOS + IR Cut filter
Horizontal Resolution	Colour: 650TVL
IR LEDs / Distance	24pcs / 15m
Lens	Fixed 3.6mm
Minimum Illumination	0Lux (IR ON)
Ingress Protection	IP66
Power	DC12V±10%
Dimensions	Ø94 x H80 mm