Securview 4 Channel H.264 Standalone Digital Video Recorders 25fps @ 720x576

The DVR feature H.264 video compression, mobile surveillance, multiple backup methods, multiple detection modes, user-friendly GUI and front panel operation as well as a number of other features which make the DVRSVIEW series great value for money. The DVR is ideal for mid to large level surveillance applications.

DVR Features:

- · High quality video Display and Recording
- Compression: H.264 for video, G.723 for Audio
- Real time CIF recording and Playback support
- Smart phone access
- USB & network backup
- Static IP as well as Dynamic IP (DHCP, Floating IP) and DDNS support
- Multi-user accessing support/ CMS/Smart Phone support

The DVR is capable of offering mobile surveillance via many popular mobile platforms, supporting popular models such as iPhone & Android (available to download from apps store), Blackberry, Symbian & Window (software available by request).













Securview 4 Channel Standalone Digital Video Recorder

	SECURVIEW 1 2 7 1
Model No	DVRSVIEW4V3
Operating System	Embedded Linux
Video Input	4CH composite Video BNC
Video Output	1 BNC,1 VGA Output VGA Resolution 1024x780
Audio Input/Output	4CH Input and 1CH Output
Display Resolution	720x576
Recording Resolution	720x576, 720x288, 352x288
Compression	H.264 for video, G.723.1 for audio
Triplex Operation	Recording, Playback, Network
Recording Speed	100fps (352x288), 50fps (720x288), 25fps (720x576)
Recording Mode	Emergency, Schedule, Sensor, Motion, Sensor + Motion, Pre & post Alarm Recording
Search Mode	Calendar, Date & Time, Event Search, First Search, Last Search
Search Speed	x1, x2, x4, x8, x10
Alarm Input / Output	4ch / 1ch
Backup Method	USB, HDD, Network
Hard Drive Storage	SATA HDD (Max 1)
Network Protocol	Static IP, DHCP & DDNS
Network interface	10/100 Base - Tx Ethernet (RJ-45)
Network Max connector	5 users
Network Access Type	Network Client Software / Web Viewer / CMS
Mobile Surveillance	iPhone & Android (available to download from apps store), Blackberry, Symbian & Window (software available by request)
PTZ	RS485
System Operation	Front Button, USB Mouse, IR Controller
Dimension	338mm(W) X 219mm(D) X 58mm(H)
Power Consumption	Max. 30W
Power	DC12V 3.5A 50Hz/60Hz







