





Silver Outdoor Station for Apartments

INTIPADSS Features:

- 3.0" Super-twisted Nematic (STN) Display
- Durable Die-Cast Aluminium Construction with Aluminium Keypad
- 1.3 Megapixel Door Camera with Excellent Low Light/Night Time Use
- Input Buttons Feature Voice Verification
- Call Contact / Management Centre / Indoor Monitor Functions
- Support for Tamper Detection and Remote Unlock
- Adopt TCP/IP Network Standard Protocol Assigns Unique IP Address for Each Device
- Supports SNMP Network Protocol
- Door Station can Communicate to Up to 300 Indoor Monitor Terminals
- Authentication Methods: Integrated Circuit (IC) Card & Password Support
- Power Supply: 10~15VDC
- Power Consumption: Standby 1W / In Use 10W
- Dimensions (mm): 376(L) x 151(W) x 60(H)

The INTIPADSS is an excellent video intercom solution in apartment complexes and other large residential applications. This model features a durable die-cast aluminium construction for the station front plate and aluminium keypad buttons. This door station also includes voice verification on key presses for ease of access.

Specifications			
Main Processor	Embedded micro processor	Vandal proof	Support
Operation System	Embedded LINUX OS	Ethernet	10M/100Mbps Self-adaptive
Video Compression Standard	H.264	Network Protocol	TCP/IP
Input/Approaching Induction	1.3 megapixel CMOS camera	Memory	128MB
Audio Input	Microphone	Power	DC 10~15V
Audio Output	Built-in speaker	Power Consumption	Standby ≤1W, work ≤10W
Bidirectional Talk	Support dual-way bidirectional talk	Working Environments	-10°C-60°C, 10%-95%RH
LCD Resolution	3-inch STN screen, 128x64	Dimensions	76(L) x 151(W) x 60(H)mm
Operation	Digital keyboard Card Built-in IC card induction reader	Weight	1.6Kg



Call: 02 9671 6711 • Email: sales@rhino.com.au • www.rhino.com.au

Mon - Fri: 8:30am - 5pm, Sat: 9-1pm 71 Middleton Road, Villawood, NSW 2163, Australia Fax: (02) 9743 8590