



Model: NVR4PRO

Professional 4 Channel NVR



With Built-in Power Over Ethernet




This 4 channel NVR features H.264 compression which provide high quality video at a fraction of the hard disk space, motion detect recording, scheduling, alarm system integration and network feed access.

The NVR can record in real-time at 1080p full high definition across all 4 channels (1920 x 1080 at 25fps). You can adjust the recorder settings for both image quality and frame rate and when the HDD is full, the NVR will automatically record over the oldest footage. Video can be viewed from either a local machine or over the internet using a web interface or smartphone application. Backups can be made via USB flash or USB hard-drives.

Installation of IP CCTV has never been simpler with the NVR4PRO. It features a built-in Power over Ethernet (PoE) switch, supplying camera power, video, audio and more across a single network cable.



Specifications	
Main Processor	Dual-core embedded processor
IP Camera Input	4 Channel
Interface	1 HDMI, 1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Compression	H.264 / MJPEG
Resolution	1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	100fps @ 1080p / 100fps @720p / 100fps @ D1
Bit Rate	48 ~ 8192kbps
Record Mode	Manual, Schedule, Motion Detection or Alarm
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	4 channel
Relay Output	3 channel
Sync Playback	1/4
Search Mode	Time/Date, Alarm, Motion Detect & Exact time search, Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Ethernet	RJ-45 port (10/100M/1000M)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Storage	2 SATA ports (2HDDs or 1HDDs+1CD/DVD-RW), up to 8TB
USB	2 ports (1 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
Power Supply	NVR: DC12V, PoE Switch: DC48V
Power Consumption	NVR: 20W(without HDD), PoE Port: Max.15 (each)
Working Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimension (W×D×H)	1U, 375mm×285mm×50mm
Weight	2.3KG(without HDD)



Your Local Dealer: