

MEGAPIXEL PROFESSIONAL NVR KIT

WITH 8 SECURITY CAMERAS AND 2TB HARD DRIVE



* Monitor (LCD19LED) not included; available option.



The NVR8PROPACK is an easy install home/business surveillance system with a powerful set of features to help protect your property. Featuring 1.3 Megapixel Day/Night ethernet cameras with H.264 compression which provide high quality video at a fraction of the hard disk space, motion detect recording, scheduling, alarm system integration and network feed access, this package contains everything you need to record and monitor your facilities. The system has been designed to allow a quick and simple installation and comes with an easy to follow operation manual.

It even comes with an inbuilt powered network switch to keep your cameras running on a single cable, supplying power and data in one connection. The NVR can record up to 30 image frames per second per camera at 1.3 Megapixel resolution (1280 x 1024). You can adjust the recorder settings for both image quality and frame rate and when the HDD is full, the NVR will automatically record over the oldest footage. Video can be viewed from either a local machine or over the internet using a web interface or smartphone application. Backups can be made via USB flash or USB hard-drives. included.

Kit includes:

- 1x 8 Channel Network Recorder
- 2TB Hard Drive
- 4x Infrared Bullet Camera
- 4x Infrared Dome Camera
- 2x 8 Port PoE Switch
- 4x 10m Network Cable
- 2x 20m Network Cable
- 2x 30m Network Cable
- 1x 1.5m Network Cable
- 1x 1m HDMI Cable

Watch Over the Internet from Anywhere!*

This VIP Vision Surveillance System is capable of offering mobile surveillance via popular smartphone/tablet operating systems such as iOS on the iPhone & iPad, and Google Android mobile devices.

Network surveillance can also be accessed through Internet Explorer web browser.



* Broadband internet required for remote access. 2 weeks recording at 15fps at 720p resolution. Monitor optional extra not supplied with product; 6 channels shown for display purposes only. Additional cameras required for 6 channel view.



Specifications: 8 Channel Network Recorder (NVR8PRO)	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
IP Camera Input	8 Channel
Two-way Talk	1 channel Input, 1 channel Output, BNC
Interface	1 HDMI, 1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Compression	H.264 / MJPEG
Resolution	1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	400fps@D1 / 200fps@720p / 100fps@1080p
Bit Rate	48 ~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank
Alarm Input	8 Channel
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
Ethernet	RJ-45 port (10/100M/1000M)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Internal HDD	2 SATA ports (2HDDs or 1HDDs+1CD/DVD-RW), up to 8TB
Power Supply	NVR: DC12V, PoE Switch: DC48V
Power Consumption	NVR: 20W(without HDD), PoE Port: Max.15 (each)
Working Environment	-10 ~+55°C / 10~90%RH / 86~106kpa
Dimension (W×D×H)	375mm×285mm×50mm
Weight	2.3KG(without HDD)



Specification: IR Bullet Camera (VSIP1MPFBIR)	
Image Sensor	1/3" 1.3Megapixel Aptina CMOS
Effective Pixels	1280(H)×960(V)
Max. IR LEDs Length	20m
Focal Length	6mm (3.6mm,8mm optional)
Power Supply	DC12V, PoE(802.3af)
Power Consumption	<6W
Working Environment	-10°C~+60°C, 10%~90%
Ingress Protection	IP66
Dimensions	Φ64.43mm×145.02mm
Weight	370g



Specification: IR Dome Camera (VSIP1MPDIR)	
Image Sensor	1/3" 1.3 Megapixel Aptina CMOS
Effective Pixels	1280(H)×960(V)
Max. IR LEDs Length	20m
Focal Length	Fixed 3.6mm @ F1.8
Power Supply	DC12V/PoE
Power Consumption	<4W
Working Environment	-10°C~+60°C
Ingress Protection	IP66
Dimensions	Ø 114mm x 86mm
Weight	288g

Call: 02 9671 6711 • Email: sales@rhino.com.au • www.rhino.com.au



Head Office
 Mon - Fri: 8:30am - 5pm
 9 Hannabus Place, McGraths Hill,
 NSW 2756 Australia
 Fax: (02) 4577 4885

Haberfield Branch
 Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
 223 Ramsay Street, Haberfield,
 NSW 2045, Australia
 Fax: (02) 9799 2024

Villawood Branch
 Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
 71 Middleton Road, Villawood,
 NSW 2163, Australia
 Fax: (02) 9743 8590