

2.8" Camera Installation Monitor



The VSCAMTESTERv2 is a Portable 2.8" LCD Test Monitor used to test, adjust and focus surveillance cameras whilst mounted in position. The unit will automatically select the appropriate signal mode (PAL or NTSC) based on the cameras output.

The looped output allows the camera signal to remain connected to the recording system during configuration. This is useful if you have an additional installer assisting with focusing or zoom parameters.

The device supports over 20 of the most commonly used PTZ protocols, including Pelco P/D, Samsung, Panasonic and TeleEye. This allows the unit to read and display PTZ commands sent from controllers. This allows for much simpler programming of patrol routes and presets.

The included battery will operate for 11 hours on a single charge. In most cases this allows for a full days usage. Recharging the device takes only 4 hours with the included charger.

Specifications

Screen Size	2.8"
Resolution	960 x 240
Signal System	NTSC / PAL (Auto-selecting)
Brightness	200 cd/m ²
Video Input / Output	1ch BNC Input / 1ch BNC Looped Output
Test Modes	IRE and mV
Battery Life	11 hours (4 hours recharge)
PTZ Support	Reads commands sent from controller (20+ protocols)
Dimensions	166mm x 95mm x 48mm
Weight	600g



Phone 02 9671 6711

Website www.rhinoco.com.au

Email sales@rhinoco.com.au

Head Office
9 Hannabus Place, McGraths Hill,
NSW 2756, Australia

Haberfield Branch
223 Ramsay Street, Haberfield,
NSW 2045, Australia

Villawood Branch
71 Middleton Road, Villawood,
NSW 2163, Australia