

VSDVF20MIR700

Vandal Resistant 20m Infrared Dome Camera



Model		VSDVF20MIR700
General	Camera Style	Dome
	Chipset	Effio-E
	OSD Menu System	Yes
	Picture Adjustment	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
Camera	Image Sensor	1/3" Exview HAD CCD II
	Effective Pixels	976(H) x 582(V)
	Electronic Shutter	1/50 - 1/110,000
	Minimum Illumination	0.005 Lux at F2.0 / 0 Lux IR Active
	Signal Noise Ratio	>60dB
	Gain Control	Auto
	White Balance	Auto Trace WB1 / Auto Trace WB2 / Manual / Auto
	Noise Reduction	2D Digital Noise Reduction
	Digital Zoom	-
	Day/Night	Yes
	Backlight Compensation	BLC/HLC/DWDR
Lens	2.8 - 12mm Manual Varifocal	
Video	Horizontal Resolution	Colour: 700TVL / B&W: 750TVL
	Video Output	1 Vp-p / 75 Ohms
	Video Signal	PAL
Environment	Ingress Protection	IP66
	Vandal Resistant	Yes
	Maximum Infrared Range	20m
	Power Input	12VDC
	Power Consumption	< 4W
	Dimensions	Ø160 x 119mm
	Weight	1.0kg
Operating Environment	-30° to 60°C / RH80% (Max)	

Your Watchguard Dealer: