



VSDVF30MIR2.8-12

Vandal Resistant 30m Infrared Dome Camera

Model		VSDVF30MIR2.8-12
General	Camera Style	Dome
	Chipset	Effio-E
	OSD Menu System	Yes
	Picture Adjustment	Mirror/Brightness/Contrast/Sharpness/Hue/Gain
Camera	Image Sensor	1/3" Exview HAD CCD II
	Effective Pixels	976(H) x 582(V)
	Electronic Shutter	1/50 - 1/110,000
	Minimum Illumination	0.001 Lux at F2.0 / 0 Lux IR Active
	Signal Noise Ratio	>48dB
	Gain Control	Auto
	White Balance	Auto/User Defined
	Noise Reduction	2D Digital Noise Reduction
	Digital Zoom	-
	Day/Night	Yes
	Backlight Compensation	BLC/HLC
Lens	2.8 - 12mm Manual Varifocal	
Video	Horizontal Resolution	Colour: 650TVL / B&W: 700TVL
	Video Output	1 Vp-p / 75 Ohms
	Video Signal	PAL
Environment	Ingress Protection	IP66
	Vandal Resistant	Yes
	Maximum Infrared Range	30m
	Power Input	12VDC
	Power Consumption	-
	Dimensions	Ø119 x 100mm
	Weight	0.9kg
Operating Environment	-10° to 50°C / RH95% (Max)	

Your Watchguard Dealer: