

VIP VISION

Model: VSIP2MPVDIRW



2.0 Megapixel Vandal Proof Wide Dynamic 20m IR Dome



20m IR

Records directly to the camera, storing video on the SD Memory Card. No cabling or separate DVR required, supply power only.

By utilising video motion detection, up to 1 week of recording can be recorded onto a 32GB SD card



If you're looking for a true standalone surveillance system which doesn't require your cameras to be connected to a central storage device, our range of VIP Vision IP Network DVR Cameras are the answer. The camera supports internal SD card storage (up to 32Gb), meaning that all recorded footage is stored locally on the camera for retrieval at your convenience.

By utilising video motion in the camera and adjusting the bitrate, long recordings can be achieved on the internal SD card (eg. up to 1 week recording can be achieved on a 32GB SD card depending on the motion).

- Recorded footage can be reviewed on a PC without the need for expensive CMS software
- 2 Megapixel image sensors ensure high quality footage
- Low-Cost surveillance system
- Internal video storage method means the camera can be repositioned as required
- Connect to a wireless router, access point or 3G modem to connect to the camera via a network

2.0 Megapixel

Vandal Proof Wide Dynamic 20m IR Dome



Model: VSIP2MPVDIRW

- Up to 2 Megapixel resolution
- H.264/MJPEG video compression with high compression ratio
- Progressive scan CMOS
- Up to 32 GB SD/SDHC card local storage
- Two-way audio
- Power over Ethernet (POE) Support

Specifications

Image Sensor	1/3 " Progressive Scan CMOS with 120GB Wide Dynamic Range
Effective Pixels	1920 x 1080
Min. Illumination	0.1 Lux @ F1.6 (AGC On), 0 Lux with IR
Lens	2.7-9mm @ F1.2
Video Compression	H.264/MJPEG
Max. Image Resolution	1920 x 1080
Frame Rate	25fps (1920 x 1080), 25fps (1280 x 720)
Video Parameter	Saturation, Brightness, Contrast adjustable through client software or web browser
Dual Stream	YES
Storage	Support SD/SDHC, NAS (iSCSI optional)
Intelligent Alarm	Motion Detection, Video Loss, Network Disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP (SNMP, HTTPS, FTP, SIP, SRTP, 802.1x, IPv6 optional)
Alarm Input	2 channel
Alarm Output	2 channel
Power Supply	DC12V±10% / PoE
Power Consumption	7.5W maximum (with IR cut filter on)
Working Temperature	-10°C ~ 60°C
Vandal Proof	YES
Dimension	Φ140mm X 114mm
Weigh	1.4kg

Website: www.rhino.com.au Email: sales@rhino.com.au



Head Office
Mon - Fri: 8:30am - 5pm
9 Hannabus Place, McGraths Hill, NSW
2756 Australia
Tel: (02) 4577 4708 Fax: (02) 4577 4885

Haberfield Branch
Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
223 Ramsay Street, Haberfield,
NSW 2045, Australia
Tel: (02) 9716 0444 Fax: (02) 9799 2024

Villawood Branch
Mon - Fri: 8:30am - 5pm, Sat: 9-1pm
71 Middleton Road, Villawood,
NSW 2163, Australia
Tel: (02) 9743 8222 Fax: (02) 9743 8590