

VSIP3MPPTZ

3.0 Megapixel IP PTZ Dome Camera



General	Camera Style	Weatherproof PTZ Dome
	Chipset	-
	Image Sensor	1/3" 3.0 Megapixel CMOS
	Effective Pixels	2048 (H) x 1536 (V)
	Signal Noise Ratio	> 50dB
Camera	Lens	4.7 ~ 94mm (20x Optical Zoom)
	Angle of View	58° (wide) ~ 3° (tele)
	Electronic Shutter	1/1 ~ 1/30,000s
	Minimum Illumination	0.05 Lux at F1.6 (Colour) / 0.005 Lux at F1.6 (B&W)
	Day/Night	Auto (ICR) / Colour/B&W
	White Balance	Auto / ATW / Indoor / Outdoor / Manual
	Noise Reduction	2D / 3D Digital Noise Reduction
	Gain Control	Auto/Manual
	Backlight Compensation	BLC / HLC / WDR (100dB in 1080p)
	Audio Input	1 ch. Input / 1ch. Output
	Audio Compression	G.711a / G.711u (32kbps) / PCM (128kbps)
	Network Interface	RJ45 (10/100 Base-T)
	Alarm Interface	7 ch. input / 2 ch. output
	Memory Slot	MicroSD slot up to 32GB
Video	Video Compression	H.264 / MJPEG
	Resolution	3.0MP (2048x1536) / 1080p (1920x1080) / 720p (1280x720)
	Frame Rate	3.0MP (1 ~ 15fps), 1080p/720p (1 ~ 25fps)
	Bit Rate	H.264: 56K ~ 8192Kbps / MJPEG: 56K ~ 20480Kbps
	Video Output	1 channel, BNC (1.0Vp-p, 75 ohm)
Environment	Ingress Protection	IP67
	Vandal Resistant	No
	Maximum Infrared Range	N/A
	Power Input	AC 24V/3A
	Power Consumption	15W / 40W (Heater on)
	Dimensions	Ø222 x 322mm
	Weight	5.0kg
	Operating Environment	-20° to 60°C / RH90% (max)

Your VIP Vision Dealer: