

Securview Waterproof IR Camera with 360° Rotational Vandal Proof Bracket

- Weatherproof housing with vandal proof cable management design
- IP55 Weatherproof Rating
- Sun Shield Housing and Aluminium Bracket
- Fully-articulated bracket allowing 360° rotation, 180° Vertical adjustment, 180° Horizontal movement.
- Adjustable Vari-Focal Lens

Specification: VSWVF50MIR4-9			
Image Sensor	1/3" SONY Super HAD CCD	Video Output	1.0Vp-p, 75 Ohms
Pixel	752 x 582	Auto Iris	A.E.S
Horizontal Resolution	540 TVL	Lens	4~9mm Manual Varifocal Lens
Signal System	PAL	IR LEDs	48 IR LEDs
Scanning System	625 Lines 50 Fields/Sec	IR Distance	50M MAx. (Line of Sight)
Minimum Illumination	0.1 Lux	Power	12VDC (+/- 10%)
Sync System	Internal Synchronisation	Current	550mA
S/N Ratio	≥48dB (AGC Off)	Working Temperature	-10 - 45 Deg C
Electronic Shutter	Auto, 1/50 - 100,000 sec	Dimensions	160 x 100 x 97mm
Gamma Correction	0.45	Weight	1.15Kg



